



► Magnetic stirrers RSLAB-1

- 1| Stainless steel plate with or without ceramic coating.
- 2| Motor with electronic speed control, constant speed even with load changes, even with load changes.
- 3| High magnetic adhesion prevents off-centre movement of the stirring magnet.
- 4| Brushless motor guarantees a long operating life
- 5| Separate safety circuit, heating stops automatically when the temperature exceeds 350°C (Model RSLAB-1C)
- 6| Protection according to DIN EN 60529: IP42.

► With heating RSLAB-1C



Code	LBB003	LBB005
Speed range	0-1500 rpm	
Maximum stirring volume	20 L	
Temperature range	RT- 340°C	
Plate material	Ceramic	Stainless steel
Plate diameter	ø 135 mm	
Aprox. dimensions	280 x 160 x 85 mm	
Aprox. weight	2,8 Kg	

► Without heating RSLAB-1NC



Code	LBG003	LBG007
Speed range	0-1500 rpm	
Maximum stirring volume	20 L	
Plate material	Cerámica	Acero Inox.
Plate diameter	ø 135 mm	
Aprox. dimensions.	280 x 160 x 85 mm	
Aprox. weight	2,8 Kg	

► Accessories (not included)



LBM006 Adapter for round bottom flasks 50 mL



LBM009 Adapter for round bottom flasks 500 mL



LBM007 Adapter for round bottom flasks 100 mL



LBM010 Poly-block red stand with 11 holes for 4 mL tubes



LBM008 Adapter for round bottom flasks 250 mL



LBM011 Poly-block purple stand with 4 holes for 20 mL tubes



▶ Accessories (not included)



LBM012 Poly-block blue stand with 4 holes for 30 mL tubes



LBM015 Poly block yellow stand with 4 holes with 16 mL tubes



LBM013 Poly-block black stand with 4 holes for 40 mL tubes



LBM016 Blue support for 4 poly-block stands



LBM014 Poly-block green stand with 6 holes for 80 mL tubes



LBM017 Blue ring for 4 poly-block stands



LBM018 Protective cover resistant up to 135°